

HOLDEN UTE / CREWMAN / ONE TONNER SPECIFICATIONS

	175kW, 3.6 litre high performance Alloytec V6 engine			235kW, 5.7 litre Alloy Generation III V8 engine			250kW, 5.7 litre Alloy Generation III V8 engine			
Capacity (cc)	3565			5665			5665			
Compression Ratio (:1)	10.2			10.1			10.1			
Power (ECE, kW)	175 @ 6000 rpm			235 @ 5600 rpm			250 @ 5600 rpm			
Torque (ECE, Nm)	Ute Crewman One Tonner	320 @ 2800 rpm 320 @ 2400 rpm 320 @ 2400 rpm		N/A 460 @ 4000 rpm 460 @ 4000 rpm			470 @ 4800 rpm N/A N/A			
Gear ratios	Manual	Auto								
1st	4.48	3.06								
2nd	2.58	1.63								
3rd	1.63	1.00								
4th	1.19	0.70								
5th	1.00									
6th	0.75									
Reverse	3.96	2.29								
Final drive ratio	3.46:1		V6 3.08:1		V8 3.07:1					
	Ute V6†	S Ute V6	SS Ute V8	Crewman V6†	S Crewman V6	SS Crewman V8	One Tonner V6†	S One Tonner V6	SS One Tonner V8	
Brakes	Four wheel disc									
Suspension	Front	MacPherson Strut‡			MacPherson Strut					
	Rear	Independent Rear Suspension^			Multi-leaf spring					
Steering	Variable ratio Rack and pinion									
Petrol Tank (L)	70			64						
Rec Petrol Octane Rating	91 ULP									
Turning Circle (kerb to kerb, m)	11.5	11.5	11.5	12.1	12.1	12.1	12.1	12.1		
Wheelbase (mm)	2939	2939	2939	3206	3206	3206	3206	3206		
Ground Clearance (mm)	115	115	105	133	133	133	134	134		
Exterior Dimensions	Length	5052	5052	5058	5306	5306	5311	5063	5063	
	Width (including mirrors)	2046	2046	2046	2046	2046	2046	(to back of frame) 2046	(to back of frame) 2046	
	Height	1476	1476	1476	1500	1512	1513	1507	1507	
Payload Area Dimensions (mm)	Length	2193			1463					
	Width	1477			1438					
	Height	486			484					
	Width at wheel arches	1226			1226					
	Ute V6†	S Ute V6	SS Ute V8	Crewman V6†	S Crewman V6	SS Crewman V8	One Tonner V6†	S One Tonner V6	SS One Tonner V8	
Area (m2) (calculated using width at wheel arches)	2.689			1.794						
Volume (m2) (calculated using width at wheel arches)	1.307			0.868						
Kerb Mass (kg)*(Est. inc A/C at 16kg and fluids)	Manual	1535	1557	1613	1754	1755	1814	1529	1540	1581
	Auto	1538	1561	1619	1757	1758	1820	1532	1543	1587
Gross Vehicle Mass (GVM kg)	Manual	2365	2275	2275	2826	2826	2535	2826	2826	2826
	Auto	2365	2275	2275	2826	2826	2535	2826	2826	2826
Payload (kg)#	Manual	830	718	662	1072	1071	721	1297	1286	1245
	Auto	827	714	656	1069	1068	715	1294	1283	1239
Gross Combined Mass (GCM kg)	Manual	3500	3500	3715	3900	3900	3975	3900	3900	4266
	Auto	3805	3715	3715	4716	4716	4785	4716	4716	5076
Axle Loads (kg)	Front	Manual	1015	1015	1015	1180	1180	1180	1180	1180
		Auto	1015	1015	1015	1180	1180	1180	1180	1180
	Rear	Manual	1350	1260	1260	1800	1800	1460	1800	1800
		Auto	1350	1260	1260	1800	1800	1460	1800	1800
Towing (kg)	Holden approved towing package available. Towing capacity is 1600kg for all Ute models, as well as V6 manual and V8 manual Crewman and One Tonner models. 2100kg for V6 automatic Crewman and One Tonner models. 2500kg for V8 automatic Crewman and One Tonner models									
Service (km)	3000 (free) inspection, V6 -15,000 then every 15,000 or 12 months, whichever comes first. V8 - 10,000 then every 10,000 or 6 months, whichever comes first. Holden Dealer 'Tech 2' computerised analysis available for engine management system									
	‡ FE2 Sports Suspension is standard for S and SS Ute. Firmer spring rate. Revised stabiliser bar diameter. Reduced ride height. ^ FE2 Sports Suspension is standard for S and SS Ute. Firmer spring rate. Gas pressure dampers.									
	* Vehicle weights based on pre-production data. All fluids at their nominated capacity.									
	# Payload includes the mass of air conditioning. Does not include options. Deduct the mass of these from the quoted payload to obtain the available payload mass. Fitment of Holden By Design alloy wheels and low profile tyres will reduce payload capacity.									
	† Includes optional A/C									