Technical Data - Audi A4 2.0 TDI (105 kW)

Model	Audi A4 2.0 TDI with diesel particulate filter
Engine / electrics	
Engine type	Inline 4-cylinder diesel engine with VTG turbocharger, DOHC,
	TDI® direct injection
Valve gear / number of valves per cylinder	Cam followers with hydraulic valve play compensation
Displacement in cc / bore x stroke in mm / compression	1968 / 81.0 x 95.5 / 16.5
Max. power output in kW / at rpm	105 / 4200
Max. torque in Nm / at rpm	320 / 1750 — 2500
Engine management / mixture preparation	Common rail injection system, 1800 bar with piezo injectors, direct injection with eight-hole nozzles, VTG turbocharger with intercooler; swirl and tangential intake ports, regulated swirl port; Bosch EDC; volume, injection start, charge pressure, low temperature EGR control
Exhaust emission control	Oxidising catalytic converter, water-cooled exhaust gas recirculation, coated maintenance-free diesel particulate filter
Emissions rating	EU 4
Alternator in A / battery in A/Ah	150 / 340 / 70
Drive / transmission	
Drivetrain type	Front-wheel drive with electronic stabilisation program ESP
Clutch	Electronically controlled multi-plate clutch, oil-cooled
Gearbox type	Continuously variable multitronic transmission with DRP, sport program
Gear ratio in 1st gear / 2nd gear	2.478 / 1.351
Gear ratio in 3rd gear / 4th gear	0.996 / 0.782
Gear ratio in 5th gear / 6th gear	0.635 / 0.528
Gear ratio in 7th gear / 8th gear	0.443 / 0.369
Reverse gear / final drive ratio	2.998 / 5.625
Suspension / steering / brakes	
Front suspension	Five-link front suspension, upper and lower wishbones, tubular anti-roll bar
Rear suspension	Independent-wheel, trapezoidal-link rear suspension with resiliently mounted
Changing / standing ratio / truming civals in m (D100)	subframe, anti-roll bar
Steering / steering ratio / turning circle in m (D102) Brake system, front/rear	Maintenance-free rack-and-pinion steering with power assistance / 16.3 / 11.4 Dual-circuit brake system with diagonal split, ABS/EBD and ESP with brake assist; tandem brake booster; front: ventilated discs / rear: discs
Wheels / tyres	16" alloy wheels / 225/55
Performance / consumption / acoustics	<u> </u>
Top speed in km/h	210
Acceleration 0-100 km/h, s	9.4
Fuel type	Diesel, to EN 590
Fuel consumption: combined (ADR 81/01)(I/100 km)	5.8
CO2 emissions: urban / extra-urban / combined (g/km)	154
Standing / drive-past exterior noise level in dB (A)	75 / 72
Servicing / guarantee	
Servicing	12 months or 15,000km
Vehicle/paint/rust perforation guarantee	3 years with unlimited km / 3 years / 12 years
Weights / loads	
Unladen weight in kg / gross weight limit in kg	1495 / 2045
Axle load limit at front / rear in kg	1100 / 1070
Trailer load limit, unbraked in kg	750
Trailer load limit on 8% / 12% gradient, braked in kg	1900 / 1700
Roof load limit in kg / permissible nose weight in kg	18 / 21 / 24
Capacities	
Cooling system capacity (incl. heating) in I	7.5
Engine oil capacity (incl. filter) in I	5.0
Fuel tank capacity in I	65
Body / dimensions)1	-
Body type	Galvaniand unitary steel hady assumple zance at front and ""
	Galvanised, unitary steel body, crumple zones at front and rear
Number of doors / seats Prog. coefficient Cd / frontal area A in m ²	4 doors with additional side protection / 5 0.27 3 / 2.20
Drag coefficient Cd / frontal area A in m ²	
Length (L103) / width excl. mirrors (W103) / height (H100-M)	
Wheelbase (L101) / track at front/rear (W101-1/W102-2) Height of loading lip in mm (H196)	2808 / 1564 / 1551 (mm) 677
Luggage capacity in I, acc. to VDA block method (V210) (V212)	480 (with rear seat folded down: 962)

⁽V212)
1) details of dimensions with unladen vehicle weight