

Technical Data	Audi Q3 35 TFSI S tronic (110 kW)
Program for Australia	Status: 01/10/2019
Engine / electrics	
Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1395 / 74.5 x 80.0 / 10.0
Max. power output in kW / at rpm	110 / 5000
Max. torque in Nm / at rpm	250 / 1500 - 3500
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Regulated catalytic converter
Emissions standard	EU6 plus
Battery in A / Ah	380 / 68
On-board voltage 1 in volts	12
Drivetrain / transmission	
Drive type	Front-wheel drive
Clutch	Dual clutch
Transmission type	6-speed S tronic / dual clutch
Suspension / steering / brakes	
Type and design of front axle suspension	McPherson struts, front
Type and design of rear axle suspension	Four-link rear suspension
Steering	Electromechanical steering with speed-dependent power assistance
Turning circle / turning circle optional in m	11.8 / -
Brake control system	Dual-circuit brake system with ESC/ABS/EBD, brake booster, hydraulic brake assist
Tyres (basic)	235/55 R18 100V
Wheels (basic)	7.0J x 18
Performance	
Top speed in km/h	207
Governed	no
Acceleration, 0-100 km/h	9.3
Fuel type / octane value	Gasoline / 95
Fuel standard	DIN EN 228
Consumption / emissions*	
Fuel consumption, urban/extra-urban/combined in litres per 100 kilometres	9.4 / 6.0 / 7.2
CO ₂ emissions combined in grams per kilometre	164
Servicing / guarantee (Australia)	
Service interval	15,000 km / 12 months, whichever comes first
Vehicle / paint / rust perforation guarantee	3 years with unlimited mileage / 3 years / 12 years
Weights / loads	
Unladen weight without driver / with driver	1470 / 1545
Gross weight limit min. / max. in kg	2015 / 2055
Front/rear axle load limit in kg	1145
Rear axle load limit min. / max. in kg	1030 / 1080
Trailer load limit on 8% / 12% gradient, braked // unbraked; in kg	2000 / 1800 // 750
Roof load limit / permissible nose weight in kg	75 / 90
Capacities	
Cooling system capacity (incl. heating) in litres	11.5
Engine oil capacity, including filter (change volume) in litres	4.3
Fuel tank capacity in litres	58
Dimensions / body	
Body type / number of doors	- / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ²	0.32 / 2.44
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm	4485 / 1849 / 1640 / not available
Width including mirrors in mm	2024
Wheelbase / track width front/rear in mm	2677 / 1582 / 1585
Overhang angle of steel springs, front/rear in degrees	18.80 / 16.20
Height of loading edge with steel springs / air springs in mm	748 / not available
Luggage capacity behind 2nd seat bench, open / closed in l	530 / not available
Largest luggage compartment capacity - behind the 1st seat row in l	1525
Open luggage compartment - behind the 2nd seat row in l	530

* Fuel consumption and CO₂ emission figures given in ranges depend on the tyres/wheels used