

Engine.		Boss 290			
Engine type	5.4L Quad Cam 32 valve V8				
Applicable models	GT, GT-P, Pursuit				
Maximum power (DIN)	290kW @ 5500rpm				
Maximum torque (DIN)	520Nm @ 4500rpm				
Compression ratio	10.5:1				
Valve sizes	Inlet - 37mm / Exhaust - 30mm				
Bore x Stroke	90.2 x 105.8mm				
Displacement	5408cc				
Injection	Sequential Multipoint Electronic Fuel Injection				
Engine management	Powertrain Control Module incorporating Electronic Throttle Control				
Ignition	Coil-on-plug ignition with long-life platinum-iridium spark plugs				
Battery	54Ah				
Fuel.		Sedan		Ute	
Fuel tank capacity	68L		80L		
Recommended fuel	PULP (95 RON)		PULP (95 RON)		
Fuel Consumption. ¹		Sedan		Ute	
		Manual	Auto	Manual	Auto
ADR81-01 (L/100km)		14.9	15	15.3	15.1
Comparative CO2 Emissions (Grams/km)		356	357	361	360
Transmission / Ratios.		Man	Auto	Man	Auto
1st		2.98	4.17	2.98	4.17
2nd		1.78	2.34	1.78	2.34
3rd		1.30	1.52	1.30	1.52
4th		1.00	1.14	1.00	1.14
5th		0.80	0.87	0.80	0.87
6th		0.63	0.69	0.63	0.69
Reverse		2.90	3.40	2.90	3.40
Final Drive ratio		3.46	2.73	3.46	2.73
Suspension.					
Front		Performance Independent Double Wishbone Front Suspension			
Rear	- Sedan	Performance Control Blade Independent Rear Suspension			
	- Ute	Performance Rear Suspension			
Brakes.					
Performance brakes	- Front	355 x 32mm, cross drilled and slotted disc with pillar venting. Brembo four piston caliper, high performance pads and low expansion rubber hose.			
	- Rear	328 x 26 mm cross drilled disc with pillar venting. Single piston caliper finished in red with low expansion rubber hose.			
Premium Brakes	- Front	355 x 32mm cross-drilled and slotted disc with pillar venting. Brembo six piston caliper with high performance pads and low expansion rubber hose.			
	- Rear	330 x 28mm cross-drilled disc with curved venting. Brembo four piston caliper with high performance pads and low expansion rubber hoses.	328 x 26 mm cross drilled disc with pillar venting. Single piston caliper finished in red with low expansion rubber hose.		
Brake Proportioning		Bosch Electronic Brakeforce Distribution (EBD)			
ABS	- Sedan	4-channel with Traction Control			
	- Ute	4-channel with Traction Control			
Maximum Towing Capacity (kg).		Sedan		Ute	
Manual		1600kg ⁸		1600kg ⁸	
Automatic		1600kg ⁸		1600kg ⁸	

--	--	--	--	--

Exterior Dimensions (mm).		
Overall length	4944	5137
Overall width (including side mirrors)	2141	2141
Wheelbase	2829	3095
Front track	1553	1553
Rear track	1586	1547
Front overhang	948	948
Rear overhang	1189	1095
Interior Dimensions (mm).		
Front head room	1010	1010
Front leg room	1086	1086
Front shoulder room	1513	1513
Front hip room	1461	1461
Rear head room	976	-
Rear leg room	980	-
Rear shoulder room	1494	-
Vehicle Masses (kg).		
Kerb weight	1855 ⁹	1870 ⁹
Gross Vehicle Mass (GVM)	-	2335
Payload ¹⁰ . (maximum)	-	465
Front axle load (maximum)	-	1165
Rear axle load (maximum)	-	1170
Gross Combined Mass (GCM) (manual & auto)	-	3775
Cargo Dimensions (mm).		
Floor level load length	-	1818.8
Belt level load length	-	1848.0
Wheelhouse cargo width	-	1152.0
Floor & belt level rear opening width	-	1394.0
Liftover height	-	657.0
Cargo depth	-	410.1
Minimum Turning Circle (m).		
Diameter kerb-to-kerb	11.0	11.5
Capacities (L).		
Luggage capacity	504	-

1. These figures are from controlled laboratory tests conducted by the Ford Motor Company of Australia Limited to Australian Standard AS2877 - 1986 and are provided to assist you in comparing fuel consumption with other vehicles. The actual fuel consumption figures you achieve will depend, however, on many factors, including your driving habits, the prevailing conditions and your vehicle's equipment, condition and use. 8. When fitted with Genuine Ford towball and trailer wiring (sold separately). Subject to State and Territory regulations. 9. Approximate kerb weight based on GT and Pursuit (with hard tonneau) with