

FIAT® Panda

TECHNICAL SPECIFICATIONS

All dimensions are expressed in millimetres unless otherwise indicated. The information is based on data available on the date of publication. The technical specifications are valid for Australia and may vary in other international markets.

GENERAL INFORMATION

Vehicle type	5-door hatchback
--------------	------------------

ENGINE – 1.2-litre 8v PETROL

Availability	Pop
Type and description	Four-cylinder, in-line
Displacement	1,242 cm ³
Bore and stroke	70.8 × 78.9
Compression ratio	11.1:1
Power	51 kW @ 5,500 rpm
Torque	102 Nm @ 3,000 rpm
Fuel requirement	Unleaded
Fuel consumption (L/100km)	6.7 (urban), 4.3 (extra-urban), 5.2 (combined)
CO ₂ emissions (g/km)	120
Emissions class	Euro 5

TRANSMISSION

Description	Five-speed manual
Drive	Front

ENGINE – 0.9-litre TwinAir Turbo PETROL

Availability	Easy & Lounge
Type and description	Two-cylinder, in-line
Displacement	875 cm ³
Bore and stroke	80.5 × 86.0
Compression ratio	10.0:1
Power	63 kW @ 5,500 rpm
Torque	145 Nm @ 1,900 rpm
Fuel requirement	Unleaded
Fuel consumption (L/100km)	Manual: 5.0 (urban), 3.8 (extra-urban), 4.2 (combined) Dualogic: 4.8 (urban), 3.7 (extra-urban), 4.1 (combined)
CO ₂ emissions (g/km)	Manual: 99 Dualogic: 95
Emissions class	Euro 5

TRANSMISSION

Description	Five-speed manual Five-speed Dualogic transmission (robotised manual with electronic clutch and manual or automatic functioning logic by driver choice)
Drive	Front

ENGINE – 1.3-litre MultiJet2 16v Turbo DIESEL

Availability	Trekking
Type and description	Four-cylinder, in-line
Displacement	1,248 cm ³
Bore and stroke	69.6 × 82.0
Compression ratio	16.8:1
Power	55 kW @ 4,000 rpm
Torque	190 Nm @ 1,500 rpm
Fuel requirement	Diesel
Fuel consumption (L/100km)	4.8 (urban), 3.8 (extra-urban), 4.2 (combined)
CO ₂ emissions (g/km)	109
Emissions class	Euro 5

TRANSMISSION

Description	Five-speed manual
Drive	Front

SUSPENSION

Front	Independent, MacPherson type with lower transverse wishbones secured to an auxiliary crossmember
Rear	Torsion beam

STEERING

Type	Rack-and-pinion with Dualdrive electric power steering
Turning diameter (m) kerb-to-kerb	9.3 – 9.7

BRAKE SYSTEM

Type	ABS with BAS (Brake Assist System) and VDC (Vehicle Dynamic Control)
Front (mm)	Disc – 257 x 12 (Pop); Ventilated disc – 257 x 22 (Easy, Lounge, Trekking)
Rear (mm)	Drum – 203 x 38

WHEELS AND TYRES

Pop	14 x 5.5J steel with full wheel covers (175/65 R14 82T tyres)
Easy	14 x 5.5J steel with full wheel covers (175/65 R14 86T tyres)
Lounge	15 x 6.0J alloy wheels (185/55 R15 82H tyres)
Trekking	15 x 6.0J alloy wheels (175/65 R15 84T tyres)

TEMPORARY USE SPARE TYRE

Pop, Easy, Lounge	S135/80 R14 84M
Trekking	T125/80 R15 95M

WEIGHTS (tare mass – in kg)

Pop	950
Easy	985
Lounge	990
Trekking	1,040

TOWING (maximum towable weight – in kg)

Unbraked	400
Braked	800 (Pop, Easy, Lounge) 900 (Trekking)

DIMENSIONS AND CAPACITIES

Overall length	3,653 (Pop, Easy, Lounge) 3,686 (Trekking)
----------------	---

Overall width (excluding mirrors)	1,643 (Pop, Easy, Lounge) 1,672 (Trekking)
-----------------------------------	---

Overall width (including mirrors)	1,882
-----------------------------------	-------

Overall height	1,551 (Pop, Easy, Lounge) 1,605 (Trekking)
----------------	---

Wheelbase	2,300
-----------	-------

Front track	1,409 (Pop, Easy, Lounge) 1,414 (Trekking)
-------------	---

Rear track	1,407 (Pop, Easy, Lounge) 1,408 (Trekking)
------------	---

Luggage capacity

Behind rear seats	225 litres
-------------------	------------

With rear seats folded	870 litres
------------------------	------------

Fuel tank capacity	37 litres (Pop, Easy, Lounge) 35 litres (Trekking)
--------------------	---
