



FORD FOCUS ST

PERFORMANCE AND ECONOMY

Engine	Power (kW) [#]	Fuel consumption L/100 km*			
		CO ₂ (g/km)	Urban	Extra Urban	Combined
2.0-litre EcoBoost	184	172	9.5	6.0	7.3

WEIGHTS

	Kerb weight (kg) [^]	Gross Vehicle Mass (kg)	Max. Roof Load (kg)
2.0-litre EcoBoost 5-dr	1464	2025	75

DIMENSIONS: FIVE-DOOR ST

Overall length (mm)	4362
Overall width with mirrors / folded mirror (mm)	2010/1858
Overall height unladen	1471
Wheelbase (mm)	2648
Front track (min max depending wheel offset) (mm)	1544-1559
Rear track (min max depending wheel offset) (mm)	1534-1549
Luggage capacity (litres)	
5-seat mode (loaded to parcel shelf)	316
2-seat mode (loaded to roof)	1215
Luggage Compartment dimensions (mm)	
Load opening height max	616
Load opening width max	996
Lift over height at curb load condition (unladen)	697
Fuel tank capacity (litres)	
Petrol (Litres)	62

STEERING AND SUSPENSION

System	Electronic Power Assisted (EPAS)
Turning circle (m)	12.0 kerb to kerb; 12.4 wall to wall
Max steering wheel turns	1.8

CHASSIS

Front suspension	MacPherson strut with semi-isolated sub-frame
------------------	---

Rear suspension	SLA independent rear axle with control blade
-----------------	--

BRAKES

	Front	Rear
Braking	FN-floating calliper	Integrated park-brake, floating calliper
Disc/Drum dimensions (mm)	320 x 25mm	271 x 11
Piston calliper dimensions (mm)	57	37

WHEELS & TYRES

	Wheels	Tyres
Standard	8 x 18 ST Design alloy	Goodyear Eagle F1 235/40 R18

ENGINE DATA

		2.0-litre EcoBoost
Type		Inline four cylinder petrol, turbocharged, transverse
Displacement	cm ³	2000
Bore	mm	87.5
Stroke	mm	83.1
Compression ratio		9.3:1
Max power	kW	184
	at rpm	5,500
Max torque	Nm	360 (with overboost)
	at rpm	2000-4500
Valve gear		DOHC with 4 valves per cylinder
Cylinders		4 in-line
Cylinder head		Cast aluminium
Cylinder block		Cast aluminium
Camshaft drive		Twin Independent Variable Cam Timing (Ti-VCT)
Crankshaft		Cast iron, 8 counterweights, 5 main bearings
Engine management		Bosch MEDG17-I4
Fuel injection		High pressure direct injection; 150 bar injection pressure
Emission control		3-way catalyst
Emission level		Euro Stage 5 (ADR 79/04)
Turbocharger		Borg Warner single scroll fixed geometry turbocharger
Lubrication system		Pressure-fed with mechanical oil pump
System capacity with filter	litres	5.4
Cooling system		Water pump with thermostat and valves, with thermal management system
System capacity incl heater	litres	6.45
Transmission		MMT6

For news releases, related materials and high-resolution photos and video, Visit www.autonews.net.au www.media.ford.com or www.flickr.com/fordapa. Follow at www.facebook.com/fordaustralia, www.twitter.com/fordaustralia or www.youtube.com/fordapa

	6-speed manual
Gear ratios	1: 3.231 x 4.063 2: 1.952 x 4.063 3: 1.321 x 4.063 4: 1.029 x 4.063 5: 1.129 x 2.955 6: 0.943 x 2.955 R: (1.423 x 3.231) x 2.955

Performance data obtained using unleaded fuel (95 RON)

* Figures obtained from controlled tests using ADR 81/02. Actual fuel consumption and emissions will depend on many factors including driving habits, prevailing conditions and your vehicle's equipment, condition and use.

^ Represents the lightest kerb weight assuming driver at 75 kg, full fluid levels and 90% fuel levels, subject to manufacturing tolerances and options, etc., fitted.

#

About Ford Motor Company

Ford Motor Company, a global automotive industry leader based in Dearborn, Mich., manufactures or distributes automobiles across six continents. With about 187,000 employees and 62 plants worldwide, the company's automotive brands include Ford and Lincoln. The company provides financial services through Ford Motor Credit Company. For more information regarding Ford's products, please visit www.ford.com.au

Contact(s):	Wes Sherwood Ford Australia +61 3 8301 2440 wsherwoo@ford.com	Neil McDonald Ford Australia +61 3 8301 2769 nmcdon11@ford.com	Jasmine Mobarek Ford Australia +61 3 8301 2763 jmobarek@ford.com
--------------------	---	--	--