

HOLDEN CAPRICE SPECIFICATIONS

	190kW, 3.6 litre high performance Alloytec 190 V6	250kW 5.7 litre high output Gen III V8
Engine	3.6L 60-degree Double Overhead Cam V6 with 4 valves per cylinder. Sequential fuel injection. High energy, distributorless ignition. Twin knock control sensors with individual cylinder adaptive control. Onboard diagnostics. Electric cooling fan. Stainless steel exhaust	'V' Configuration. High flow, low restriction air intake. OHV design with cross flow cylinder heads. Sequential fuel injection. High energy, distributorless, ignition. Twin knock control sensors. Onboard diagnostics. Electric cooling fan. Stainless steel exhaust
	Electronic throttle control (ETC)	
	Aluminium alloy block and cylinder heads	
	Low restriction air intake with acoustic dampening chambers.	High flow, low restriction air intake
	Aluminium oil pan	
	Continuously variable camshaft phasing for inlet and exhaust cams. Variable intake manifold	
		High performance dual exhaust
	Coil-on-plug	Coil-per-cylinder
	Cross-bolted main bearings. 6-bolt	
Bore x stroke (mm)	94 x 85.6	99 x 92
Capacity (cc)	3565	5665
Compression ratio (:1)	10.2	10.1
Power (ECE, kW)	190 @ 6500rpm	250 @ 5600rpm
Torque (ECE, Nm)	340 @ 3200rpm	470 @ 4800rpm
Gear ratios	5 speed	4 speed
	1st 3.42	3.06
	2nd 2.215	1.63
	3rd 1.60	1.00
	4th 1.0	0.70
	5th 0.75	
	Final drive ratio 2.87	3.07
Recommended petrol octane	91 (ULP)	

Petrol tank (L)	75			
Brakes	Four wheel disc. Ventilated front disc and finned caliper			
Anti-lock Braking System (ABS)	4 channel			
Traction Control (TC)	When sensors detect imminent rear wheel spin, engine torque is reduced. If one wheel is about to spin, braking is applied to transfer torque to wheel with better traction.			
Kerb weight (Est. kg)	1728	1772		
Suspension	Front: MacPherson strut. Direct acting stabiliser bar. Progressive rate coil springs. Rear: Control-Link Independent Rear Suspension (IRS). Semi-trailing arm. Progressive rate miniblock coil springs. Stabiliser bar			
Steering track (mm)	Variable ratio rack and pinion Front: 1559 Rear: 1577			
Turn circle (kerb to kerb, m)	11.5			
Wheelbase (mm)	2939			
Exterior dimensions (mm)	Length 5193	Width 1847 2046 (Mirrors)	Height 1444	Ground clearance 105
Interior dimensions (mm)	Leg	Shoulder	Head	Hip
	Front	1070	1510	992
	Rear	1099	1499	981
Cargo (L)	530			
Towing (kg)	Holden approved 1200kg, 1600kg and 2100kg			
Service	V6	3000km (at no cost) inspection. 15,000km then every 15,000km or 12 months, whichever comes first.		
	V8	3000km (at no cost) inspection. 10,000km then every 10,000km or 6 months, whichever comes first.		
	Maintenance-free, long life, accessory drive belt with automatic tensioner. Dual belt on V8. Holden Dealer 'Tech 2' computerised analysis available for engine management system.			