

# TECHNICAL SPECIFICATIONS

	180kW <sup>#</sup> 3.6 litre Vapour Injection LPG V6 engine	260kW <sup>**</sup> 6.0 litre Generation IV Alloy V8 engine		
Engine	3.6L 60-degree Double Overhead Cam V6 with 4 valves per cylinder. Cylinder controlled, Spark optimised, LPG Vapour Injection. Twin knock control sensors with individual high compression cylinder adaptive control. Euro on-board diagnostics	6.0L 90-degree OHV V8. Cross flow cylinder heads. Twin knock control sensors. On-board diagnostics. Active Fuel Management (AFM)		
	Continuously variable camshaft phasing for inlet and exhaust valves	Central plenum with individual symmetrical runners		
Capacity (cc)	3564	5967		
Compression ratio (:1)	12.2	10.4		
Power (ECE, kW) <sup>#</sup>	180kW @ 6000rpm	260kW @ 5600rpm – Auto		
Torque (ECE, Nm) <sup>#</sup>	320Nm @ 2000rpm	517Nm @ 4400rpm – Auto		
Exhaust system – stainless steel	Single exhaust outlet	Quad exhaust outlet		
Gear ratios	6sp Auto	6sp Auto		
	1st 4.07	4.03		
	2nd 2.37	2.36		
	3rd 1.55	1.53		
	4th 1.16	1.15		
	5th 0.85	0.85		
	6th 0.67	0.67		
	Final ratio 3.27	2.92		
Recommended fuel	91 RON ULP. Note that using 95 RON (PULP) or higher may result in improved engine performance and efficiency (6.0L Gen IV V8). E85 can be used on the 6.0L Gen IV V8 engine, LPG to be used for LPG variants			
Fuel tank capacity (L)	71 (Petrol), 84.4 (LPG)			
Brakes	4-wheel disc. Ventilated discs – front and rear. Twin piston alloy front calliper, single piston alloy rear calliper			
Electronic Stability Control (ESC)	Incorporating: Anti-lock Braking System (ABS), Electronic Brakeforce Distribution (EBD), Electronic Brake Assist (EBA), Traction Control System (TCS)			
Suspension	Front: Direct acting stabiliser bar. Coil springs Rear: Multi-Link Independent Rear Suspension (IRS) Semi-trailing arm. Mini-block coil springs. Stabiliser bar			
Steering	Electric assisted constant ratio rack and pinion steering			
Track (mm)	Front	Rear		
	1593	1608		
Turn circle (kerb to kerb, m)	11.6			
Wheelbase (mm)	3009			
Exterior dimensions (mm)	Length	Width (excluding mirrors)	Height	
	5160	1898	1470	
Interior dimensions (mm)	Leg	Shoulder	Head	Hip
	Front 1074	1502	985	1454
	Rear 1097	1497	965	1472
Cargo volume (L)	531			
Towing (kg)	Holden approved 1200, 1600 and 2100 towing equipment is available. See your Holden Dealer for details			
Service	The complimentary inspection is due at 3000km or 3 months (whichever occurs first). The first service is due at 15,000km or 9 months (whichever occurs first) and then every 15,000km or 9 months (whichever occurs first) since the last service. Additional services may be required under certain driving conditions such as when towing (refer to Owner's handbook)			

<sup>#</sup> Maximum figures as per ECE regulations  
<sup>\*</sup> Figure quoted using 98 RON (PULP)