

TECHNICAL SPECIFICATIONS

	210kW, [#] 3.6 litre SIDI Direct Injection V6 engine		260/270kW, ^{**} 6.0 litre Generation IV Alloy V8 engine	
Engine	3.6L 60-degree Double Overhead Cam V6 with 4 valves per cylinder. Twin knock control sensors with individual cylinder adaptive control. On-board diagnostics. Spark Ignition Direct Injection (SIDI)		6.0L 90-degree OHV V8. Cross-flow cylinder heads. Twin knock control sensors. On-board diagnostics. Active Fuel Management (AFM) [†]	
	Continuously variable camshaft phasing for inlet and exhaust valves		Central plenum with individual symmetrical runners	
Capacity (cc)	3564		5967	
Compression ratio (:1)	11.5		10.4	
Power (ECE, kW)[#]	210kW @ 6700rpm		260kW @ 5600rpm – Auto 270kW @ 5600rpm – Man	
Torque (ECE, Nm)[#]	350Nm @ 2800rpm		517Nm @ 4400rpm – Auto 530Nm @ 4400rpm – Man	
Exhaust system – chrome	Dual exhaust outlet		Quad exhaust outlet	
Gear ratios	6sp Man	6sp Auto	6sp Man	6sp Auto
	1st 4.48	4.07	3.01	4.03
	2nd 2.58	2.37	2.07	2.36
	3rd 1.68	1.55	1.43	1.53
	4th 1.19	1.16	1	1.15
	5th 1	0.85	0.71	0.85
	6th 0.75	0.67	0.57	0.67
	Final ratio 3.27	3.27	3.45	2.92
Recommended fuel	91 RON ULP. Note that using 95 RON (PULP) or higher may result in improved engine performance and efficiency. E85 can be used on the 3.6L SIDI V6 and 6.0L Gen IV V8 engines			
Fuel tank capacity (L)	71 (Petrol)			
Brakes	4-wheel disc. Ventilated discs – front and rear. Twin piston alloy front calliper, single piston alloy rear calliper SSV Redline: Brembo [®] high performance brakes, with 4 piston front callipers and upgraded discs			
Electronic Stability Control (ESC)	Incorporating: Anti-lock Braking System (ABS), Electronic Brakeforce Distribution (EBD), Electronic Brake Assist (EBA), Traction Control System (TCS)			
Suspension	Front: Direct acting stabiliser bar. Coil spring Rear: Multi-Link Independent Rear Suspension (IRS). Coil spring. Stabiliser bar			
Steering	Electric assisted constant ratio rack and pinion steering			
Track (mm)[^]	Front	Rear		
	Ute 1600	1614		
	SV6, SS, SS V-Series 1592	1606		
	SS V-Series Redline 1593	1588		
Turn circle (kerb to kerb, m)	11.6			
Wheelbase (mm)[^]	3009			
Exterior dimensions (mm)[^]	Length	Width (excluding mirrors)	Height	
	5062 (Base) 5083 (Sports)	1898	1494	
Interior dimensions (mm)[^]	Leg	Shoulder	Head	Hip
	Front 1074	1502	985	1454
Towing (kg)	1600 Holden approved 1600 towing equipment is available. See your Holden Dealer for details			
Service	The complimentary inspection is due at 3000km or 3 months (whichever occurs first). The first service is due at 15,000km or 9 months (whichever occurs first) and then every 15,000km or 9 months (whichever occurs first) since the last service. Additional services may be required under certain driving conditions such as when towing (refer to Owner's handbook)			

[#] Maximum figures as per ECE regulations
^{*} Figure quoted using 98 RON (PULP)
[†] Automatic transmission only
[^] Dimensions may vary from model to model