



# Specifications.

## MINI One.

## MINI One Automatic.

Body		MINI One	MINI One Automatic
Number of doors/seats		3 / 4	3 / 4
Length/width/height (empty)	mm	3821 / 1727 / 1414	3821 / 1727 / 1414
Wheelbase	mm	2495	2495
Track width, front/rear	mm	1501 / 1501	1501 / 1501
Turning circle	m	10.8	10.8
Fuel tank capacity	approx. l	40	40
Cooling system incl. heating	l	5.3	5.7
Engine oil	l	4.25	4.25
Transmission oil incl. drivetrain	l	lifetime filling	lifetime filling
Unladen weight according to DIN/EU <sup>1)</sup>	kg	1090 / 1165	1120 / 1195
Payload according to DIN	kg	450	450
Permitted gross vehicle weight	kg	1570	1600
Permitted axle loads, front/rear	kg	865 / 765	865 / 765
Permitted trailer load braked (12 %) / unbraked	kg	- / -	- / -
Permitted roof load/permitted download	kg	60 / -	60 / -
Luggage compartment capacity	l	211	211
Aerodynamic drag $c_x / A / c_x \times A$	- / m <sup>2</sup> / m <sup>2</sup>	0.28 / 2.07 / 0.58	0.28 / 2.07 / 0.58
<b>Engine</b>			
Type/no. of cylinders/valves		in-line / 3 / 4	in-line / 3 / 4
Engine control		MEVD 17.2.3	MEVD 17.2.3
Capacity	cc	1198	1198
Bore/stroke	mm	78.0 / 83.6	78.0 / 83.6
Compression	:1	11.0	11.0
Fuel	RON	91-98	91-98
Output	kW/bhp	75 / 102	75 / 102
at engine speed	rpm	4250 - 6000	4250 - 6000
Torque	Nm	180	180
at engine speed	rpm	1400 - 4000	1400 - 4000
<b>Electrical system</b>			
Battery/installation	Ah / -	70 / engine compartment	70 / engine compartment
Alternator	A	150	150
<b>Suspension</b>			
Front wheel suspension		Single-joint McPherson spring strut axle with aluminium swivel bearing and anti-dive control	
Rear wheel suspension		Multilink axle with weight-optimised trailing arms	
Brakes, front		disc, vented	disc, vented
Rear brakes		disc	disc
Driving stability systems		Hydraulic 2-circuit brake system with anti-lock brakes (ABS), electronic brake force distribution (EBD) and Cornering Brake Control (CBC), Dynamic Stability Control (DSC) with brake assistant, hill start assistant, brake dry function, Fading Brake Support, Dynamic Traction Control (DTC) and Electronic Differential Lock Control (EDLC). Handbrake impacts mechanically on rear wheels	
Steering		Electrically assisted EPS unit with Servotronic function	
Overall steering ratio	:1	14.2	14.2
Tyres		175/65 R15 84H	175/65 R15 84H
Rims		5.5J x 15 steel	5.5J x 15 steel
<b>Transmission</b>			
Transmission type		6-speed manual transmission	6-speed automatic transmission
Gear ratio	I	:1 3.615	4.459
	II	:1 1.952	2.508
	III	:1 1.241	1.556
	IV	:1 0.969	1.142
	V	:1 0.806	0.851
	VI	:1 0.683	0.672
Reverse gear	:1	3.538	3.185
Final drive ratio	:1	3.632	3.683
<b>Driving performance figures</b>			
Power-to-weight ratio according to DIN	kg/kW	14.5	14.9
Power output per litre	kW/l	62.6	62.6
Acceleration	0-100 km/h	s 9.9	10.2
	0-1000 m	s <sup>2)</sup>	<sup>2)</sup>
in 4th/5th gear	80-120 km/h	s <sup>2)</sup> / 11.8	- / -
Top speed	km/h	195	195
<b>Fuel consumption in EU cycle <sup>3)</sup></b>			
Urban	l/100 km	5.7 - 5.8	5.8 - 5.9
Extra-urban	l/100 km	4.0 - 4.0	4.2 - 4.3
Total	l/100 km	4.6 - 4.7	4.8 - 4.9
CO <sub>2</sub>	g/km	108 - 109	112 - 114
<b>Other</b>			
Emission rating		EU6	EU6
Ground clearance (empty)	mm	124	124

Specifications apply to ACEA markets / data relevant to homologation applicable in part only to Germany (weight)

<sup>1)</sup> Weight of road-ready automobile (DIN) plus 75 kg for driver and luggage

<sup>2)</sup> Details not yet available

<sup>3)</sup> Dependent on tyre format selected