

Features & Specification

4x2

Features			Single Cab Chassis DX	Freestyle Cab Chassis DX+	Freestyle Cab Utility DX+	Dual Cab Utility DX
Transmission						
5-speed manual			X	X	X	X
5-speed automatic			-	-	-	-
Exterior						
Styled steel wheels			-	X	X	X
Alloy wheels			X	-	-	-
Power windows			-	X	X	-
Freestyle door system			-	X	X	-
Manual exterior mirrors			X	X	-	X
Power exterior mirrors			-	-	X	-
Front mudflaps			X	X	X	X
Rear mudflaps			-	-	X	X
Chrome exterior mirrors, door and tailgate handles			-	-	-	-
Side steps (aluminium finish)			-	-	-	-
Wheel arch flares (black)			-	X	X	X
Wheel arch flares (painted in high gloss)			-	-	-	-
Automatic locking/remote free wheel hubs			-	-	-	-
Utility features:	cab guard/load rest		-	-	X	X
	centre tailgate release		-	-	X	X
	exterior rope rails/hooks		-	-	X	X
	interior rope hooks		-	-	-	-
	double wall construction		-	-	X	X
Front bumper (black)			X	X	X	X
Front bumper (body coloured)			-	-	-	-
Rear step bumper (black)			-	-	X	X
Rear step bumper (chrome)			-	-	-	-
Underbody impact protection			-	-	-	-
Green tinted windscreen and side windows			X	X	X	X

Lockable fuel filler cap			X	X	-	-
Lights						
Halogen headlamps			X	X	X	X
Front fog-lamps			-	-	-	-
Interior dome lamp			X	X	X	X
Interior map reading spot lamps			-	X	X	X
Illuminated power window switch (driver)			-	X	X	-
Illuminated ignition key surround			X	X	X	X
Lights-left-on sound warning			X	X	X	X
Instrument panel light dimmer			X	X	X	X
Instrumentation						
Tachometer, temperature gauge and electronic odometer			X	X	X	X
Low fuel warning light			X	X	X	X
Automatic transmission indicator			-	-	-	-
Digital clock			X	X	X	X
Critical function warning lights			X	X	X	X
Interior						
4-speed heater/demister			X	X	X	X
Tilt adjustable steering wheel			X	X	X	X
Front 2-speed wipers with variable intermittent function			X	X	X	X
Interior release for fuel filler door			-	-	X	X
Cloth seat trim			X	-	-	X
'Sports mesh' cloth seat trim			-	X	X	-
Front bench seat with:	adjustable head restraints		X	-	-	-
	slide adjustment		X	-	-	-
	centre fold down armrest		X	-	-	-
Front bucket seats with:	adjustable head restraints		opt	X	X	X
	rake and slide adjustment		opt	X	X	X
	full recline function		-	X	X	X
	seat back pocket (passenger)		-	X	X	-

Rear bench seat with:	integral head restraints	-	-	-	X	
	centre fold down armrest	-	-	-	X	
Rear foldable 'jump' seats (with 2 seat-belts)		-	X	X	-	
Vinyl floor covering		X	-	-	X	
Carpet floor covering with driver's vinyl heel pad		-	X	X	-	
Front door map pockets		X	X	X	X	
Centre dash storage box		X	X	X	X	
Centre armrest console with dual compartments		-	X	X	-	
Lockable (and illuminated) glove box		X	X	X	X	
Rear door storage bins		-	X	X	-	
Rear under-floor storage bins		-	X	X	-	
Vanity mirror (front passenger)		-	X	X	X	
Rear window demister		-	X	X	X	
Auxiliary power outlet		X	X	X	X	
Front passenger assist grip		X	X	X	X	
Rear passenger assist grips		-	-	-	X	
Driver's left footrest		X	X	X	X	
Cigarette lighter and ashtray		X	X	X	X	
Cupholders		X	X	X	X	
Audio						
AM/FM digital tuner		X	X	X	X	
CD player, single disc (MP3 compatible)		X	X	X	X	
CD player, in-dash 6-disc (MP3 compatible)		-	-	-	-	
Speakers, number of			2	4	4	2
Safety & Theft Prevention						
Anti-lock Braking System (ABS) with Electronic Brake-force Distribution (EBD)		-	opt	opt	opt	
Limited Slip Differential (LSD)		-	-	-	-	
Front SRS airbags (driver and passenger)		X	X	X	X	

Front seat-belts with pretensioners and load-limiters			X	X	X	X
Front seat-belts with height adjustable shoulder anchorages			-	-	-	X
Remote central locking (2 transmitters with retractable key)			X	X	X	X
Engine immobiliser			X	X	X	X
One touch (up and down) power window (driver)			-	X	X	-
Child restraint anchor points			-	-	-	X
Childproof rear door locks			-	-	-	X
Left-hand-side convex (wide angle) exterior mirror			X	X	X	X
Day/night rear vision mirror			X	X	X	X
High mount stop lamp			-	-	-	-
Side impact door beams			X	X	X	X
Specifications						
			4x2			
			Single Cab Chassis DX	Freestyle Cab Chassis DX+	Freestyle Cab Utility DX+	Dual Cab Utility DX
Engine						
Engine type			2.5 litre in-line 4 cylinder 16 valve DOHC intercooled turbo diesel	3.0 litre in-line 4 cylinder 16 valve DOHC intercooled turbo diesel	3.0 litre in-line 4 cylinder 16 valve DOHC intercooled turbo diesel	3.0 litre in-line 4 cylinder 16 valve DOHC intercooled turbo diesel
Engine capacity		cc	2,499	2,953	2,953	2,953
Bore and stroke		mm	93 x 92	96 x 102	96 x 102	96 x 102
Compression ratio			18.0 : 1	18.0 : 1	18.0 : 1	18.0 : 1
Maximum power		kW	105 @ 3,500rpm	115 @ 3,200rpm	115 @ 3,200rpm	115 @ 3,200rpm
Maximum torque		Nm	330 @ 1,800rpm	380 @ 1,800rpm	380 @ 1,800rpm	380 @ 1,800rpm
Throttle control			Electronic (drive-by-wire)	Electronic (drive-by-wire)	Electronic (drive-by-wire)	Electronic (drive-by-wire)
Fuel system			Common-rail, electronic direct injection	Common-rail, electronic direct injection	Common-rail, electronic direct injection	Common-rail, electronic direct injection
Fuel tank capacity		litres	70	70	70	70
Fuel consumption1	man (combined)	l/100km	8.3	9.2	9.2	9.2
	auto (combined)	l/100km	-	-	-	-

Recommended fuel			Diesel	Diesel	Diesel	Diesel
Alternator		volts-amps	12V-70A	12V-70A	12V-70A	12V-70A
Transmission Ratios						
1st	man/auto		3.905/-	3.905/-	3.905/-	3.905/-
2nd			2.248/-	2.248/-	2.248/-	2.248/-
3rd			1.491/-	1.491/-	1.491/-	1.491/-
4th			1.000/-	1.000/-	1.000/-	1.000/-
5th			0.800/-	0.800/-	0.800/-	0.800/-
Reverse			3.391/-	3.391/-	3.391/-	3.391/-
Final drive			3.416/-	3.727/-	3.727/-	3.727/-
Transfer gear	high		-	-	-	-
	low		-	-	-	-
Chassis & Suspension						
Brakes			Dual circuit hydraulic with vacuum servo assistance and tandem master cylinder	Dual circuit hydraulic with vacuum servo assistance and tandem master cylinder	Dual circuit hydraulic with vacuum servo assistance and tandem master cylinder	Dual circuit hydraulic with vacuum servo assistance and tandem master cylinder
Brake type	front		Ventilated disc	Ventilated disc	Ventilated disc	Ventilated disc
	rear		Drum with automatic adjust and load sensing proportioning valve	Drum with automatic adjust and load sensing proportioning valve	Drum with automatic adjust and load sensing proportioning valve	Drum with automatic adjust and load sensing proportioning valve
Suspension	front		Independent double wishbone with torsion bar and double acting shock absorbers	Independent double wishbone with torsion bar and double acting shock absorbers	Independent double wishbone with torsion bar and double acting shock absorbers	Independent double wishbone with torsion bar and double acting shock absorbers
	rear		Rigid axle with leaf springs and bias mounted double acting shock absorbers	Rigid axle with leaf springs and bias mounted double acting shock absorbers	Rigid axle with leaf springs and bias mounted double acting shock absorbers	Rigid axle with leaf springs and bias mounted double acting shock absorbers

Power Steering			Power assisted (engine revolution sensing) ball and nut	Power assisted (engine revolution sensing) ball and nut	Power assisted (engine revolution sensing) ball and nut	Power assisted (engine revolution sensing) ball and nut
Turning circle	kerb to kerb	m	12	12.6	12.6	12.6
Tyres			215/70R15C 106/104S	235/75R15 109S	235/75R15 109S	235/75R15 109S
Wheels			15 x 6.5 J (alloy)	15 x 6.5 JJ (styled steel)	15 x 6.5 JJ (styled steel)	15 x 6.5 JJ (styled steel)
Spare tyre/wheel			Full size (styled steel)	Full size (styled steel)	Full size (styled steel)	Full size (styled steel)
Dimensions						
Overall length		mm	4,841	4,841	5,169	5,169
Overall width		mm	1,715	1,807	1,807	1,807
Overall height		mm	1,622	1,743	1,743	1,755
Wheelbase		mm	2,985	3,000	3,000	3,000
Ground clearance	unladen	mm	181	207	207	207
Track	front	mm	1,445	1,445	1,445	1,445
	rear	mm	1,450	1,440	1,440	1,440
Tray length		mm	-	-	1,753	1,530
Tray width		mm	-	-	1,456	1,456
Tray height		mm	-	-	465	465
Tray floor height to ground		mm	-	-	797	798
Back of cab to rear axle		mm	1,193	680	680	457
Overhang	front	mm	884	884	884	884
	rear	mm	975	960	1,285	1,285
Wading depth		mm	400	750	750	750
Approach angle		degrees	24	32	32	32
Departure angle		degrees	26	27	26	26
Ramp breakover angle		degrees	21	28	28	28
Leg room	front	mm	1,049	1,068	1,068	1,068
Shoulder room	front	mm	1,405	1,405	1,405	1,405
Head room	front	mm	1,012	1,012	1,012	1,012
Weights & Capacities						
Gross Combined Mass (GCM) ²	man	kg	4,500	5,500	5,500	5,500
	auto	kg	-	-	-	-
Gross Vehicle Mass (GVM)	man	kg	2,844	2,936	2,936	2,899
	auto	kg	-	-	-	-
Kerb weight	man	kg	1,434-1,436	1,562-1,566	1,696-1,701	1,730-1,735
	auto	kg	-	-	-	-
Payload ³	man	kg	1,410-1,408	1,374-1,370	1,240-1,235	1,169-1,164
	auto	kg	-	-	-	-
Axle capacity	front	kg	1,170	1,430	1,430	1,430
	rear	kg	1,860	1,850	1,850	1,850
Towing capacity ⁴	braked	kg	2,250	2,500	2,500	2,500
	unbraked	kg	750	750	750	750
Seating capacity			2 or 3	4	4	5

1 Fuel consumption figures are based on ADR81/01 test results. They are useful in comparing the fuel consumption of different vehicles. They may not be the fuel consumption achieved in practice. This will depend on traffic and road conditions and how the vehicle is driven.
2 Gross Combined Mass (GCM) is the total permissible combined weight of the vehicle and trailer/caravan being towed including occupants, fuel and cargo.
3 The weight of any vehicle occupants, options, accessories, modifications, cargo and towball downforce must be included when calculating payload weight.
4 Subject to State or Territory regulations. When towing more than 1,800kg a load-levelling device must be fitted.

4x4

Features		4x4					
		Single Cab Chassis DX	Freestyle Cab Chassis DX+	Freestyle Cab Utility DX+	Freestyle Cab Utility SDX	Dual Cab Utility DX	Dual Cab Utility SDX
Transmission							
5-speed manual		X	X	X	X	X	X
5-speed automatic		-	-	-	-	-	opt
Exterior							
Styled steel wheels		X	X	X	-	X	-
Alloy wheels		-	-	-	X	-	X
Power windows		-	X	X	X	-	X
Freestyle door system		-	X	X	X	-	-
Manual exterior mirrors		X	X	-	-	X	-
Power exterior mirrors		-	-	X	X	-	X
Front mudflaps		X	X	X	X	X	X
Rear mudflaps		-	-	X	X	X	X
Chrome exterior mirrors, door and tailgate handles		-	-	-	X	-	X
Side steps (aluminium finish)		-	-	-	X	-	X
Wheel arch flares (black)		X	X	X	-	X	-
Wheel arch flares (painted in high gloss)		-	-	-	X	-	X
Automatic locking/remote free wheel hubs		X	X	X	X	X	X
Utility features:	cab guard/load rest	-	-	X	-	X	-
	centre tailgate	-	-	X	X	X	X

	release						
	exterior rope rails/hooks	-	-	X	-	X	-
	interior rope hooks	-	-	-	X	-	X
	double wall construction	-	-	X	X	X	X
Front bumper (black)		X	X	X	-	X	-
Front bumper (body coloured)		-	-	-	X	-	X
Rear step bumper (black)		-	-	X	-	X	-
Rear step bumper (chrome)		-	-	-	X	-	X
Underbody impact protection		X	X	X	X	X	X
Green tinted windscreen and side windows		X	X	X	X	X	X
Lockable fuel filler cap		X	X	-	-	-	-
Lights							
Halogen headlamps		X	X	X	X	X	X
Front fog-lamps		-	-	-	X	-	X
Interior dome lamp		X	X	X	X	X	X
Interior map reading spot lamps		-	X	X	X	X	X
Illuminated power window switch (driver)		-	X	X	X	-	X
Illuminated ignition key surround		X	X	X	X	X	X
Lights-left-on sound warning		X	X	X	X	X	X
Instrument panel light dimmer		X	X	X	X	X	X
Instrumentation							
Tachometer, temperature gauge and electronic odometer		X	X	X	X	X	X
Low fuel warning light		X	X	X	X	X	X
Automatic transmission indicator in instrument cluster		-	-	-	-	-	opt

Digital clock		X	X	X	X	X	X
Critical function warning lights		X	X	X	X	X	X
Interior							
4-speed heater/demister		X	X	X	X	X	X
Tilt adjustable steering wheel		X	X	X	X	X	X
Front 2-speed wipers with variable intermittent function		X	X	X	X	X	X
Interior release for fuel filler door		-	-	X	X	X	X
Cloth seat trim		X	-	-	-	X	-
'Sports mesh' cloth seat trim		-	X	X	X	-	X
Front bench seat with:	adjustable head restraints	X	-	-	-	-	-
	slide adjustment	X	-	-	-	-	-
	centre fold down armrest	X	-	-	-	-	-
Front bucket seats with:	adjustable head restraints	opt	X	X	X	X	X
	rake and slide adjustment	opt	X	X	X	X	X
	full recline function	-	X	X	X	X	X
	seat back pocket (passenger)	-	X	X	X	-	X
Rear bench seat with:	integral head restraints	-	-	-	-	X	X
	centre fold down armrest	-	-	-	-	X	X
Rear foldable 'jump' seats (with 2 seatbelts)		-	X	X	X	-	-
Vinyl floor covering		X	-	-	-	X	-
Carpet floor covering with driver's vinyl heel pad		-	X	X	X	-	X
Front door map pockets		X	X	X	X	X	X
Centre dash storage box		X	X	X	X	X	X
Centre armrest console with dual compartments		-	X	X	X	-	X

Lockable (and illuminated) glove box		X	X	X	X	X	X
Rear door storage bins		-	X	X	X	-	-
Rear under-floor storage bins		-	X	X	X	-	-
Vanity mirror (front passenger)		-	X	X	X	X	X
Rear window demister		-	X	X	X	X	X
Auxiliary power outlet		X	X	X	X	X	X
Front passenger assist grip		X	X	X	X	X	X
Rear passenger assist grips		-	-	-	-	X	X
Driver's left footrest		X	X	X	X	X	X
Cigarette lighter and ashtray		X	X	X	X	X	X
Cupholders		X	X	X	X	X	X
Audio							
AM/FM digital tuner		X	X	X	X	X	X
CD player, single disc (MP3 compatible)		X	X	X	-	X	-
CD player, in-dash 6-disc (MP3 compatible)		-	-	-	X	-	X
Speakers, number of			2	4	4	6	2
							6
Safety & Theft Prevention							
Anti-lock Braking System (ABS) with EBD		opt	opt	opt	X	opt	X
Limited Slip Differential (LSD)		X	X	X	X	X	X
Front SRS airbags (driver and passenger)		opt	X	X	X	X	X
Front seat-belts with pretensioners and load-limiters		opt	X	X	X	X	X
Front seat-belts with height adjustable shoulder anchorages		-	-	-	-	X	X
Remote central locking (2 transmitters with retractable key)		X	X	X	X	X	X
Engine		X	X	X	X	X	X

immobiliser							
One touch (up and down) power window (driver)		-	X	X	X	-	X
Child restraint anchor points		-	-	-	-	X	X
Childproof rear door locks		-	-	-	-	X	X
Left-hand-side convex (wide angle) exterior mirror		X	X	X	X	X	X
Day/night rear vision mirror		X	X	X	X	X	X
High mount stop lamp		-	-	-	X	-	X
Side impact door beams		X	X	X	X	X	X

Specifications							
		4x4					
		Single Cab Chassis DX	Freestyle Cab Chassis DX+	Freestyle Cab Utility DX+	Freestyle Cab Utility SDX	Dual Cab Utility DX	Dual Cab Utility SDX
Engine							
Engine type		3.0 litre in-line 4 cylinder 16 valve DOHC intercooled turbo diesel	3.0 litre in-line 4 cylinder 16 valve DOHC intercooled turbo diesel	3.0 litre in-line 4 cylinder 16 valve DOHC intercooled turbo diesel	3.0 litre in-line 4 cylinder 16 valve DOHC intercooled turbo diesel	3.0 litre in-line 4 cylinder 16 valve DOHC intercooled turbo diesel	3.0 litre in-line 4 cylinder 16 valve DOHC intercooled turbo diesel
Engine capacity		2,953	2,953	2,953	2,953	2,953	2,953
Bore and stroke		96 x 102	96 x 102	96 x 102	96 x 102	96 x 102	96 x 102
Compression ratio		18.0 : 1	18.0 : 1	18.0 : 1	18.0 : 1	18.0 : 1	18.0 : 1
Maximum power		115 @ 3,200rpm	115 @ 3,200rpm	115 @ 3,200rpm	115 @ 3,200rpm	115 @ 3,200rpm	115 @ 3,200rpm
Maximum torque		380 @ 1,800rpm	380 @ 1,800rpm	380 @ 1,800rpm	380 @ 1,800rpm	380 @ 1,800rpm	380 @ 1,800rpm
Throttle control		Electronic (drive-by-wire)	Electronic (drive-by-wire)	Electronic (drive-by-wire)	Electronic (drive-by-wire)	Electronic (drive-by-wire)	Electronic (drive-by-wire)
Fuel system		Common-rail, electronic direct injection	Common-rail, electronic direct injection	Common-rail, electronic direct injection	Common-rail, electronic direct injection	Common-rail, electronic direct injection	Common-rail, electronic direct injection
Fuel tank capacity		70	70	70	70	70	70
Fuel consumption1	man (combined)	9.2	9.2	9.2	9.2	9.2	9.2
	auto (combined)	-	-	-	-	-	10.4

Power Steering		Power assisted (engine revolution sensing) ball and nut	Power assisted (engine revolution sensing) ball and nut	Power assisted (engine revolution sensing) ball and nut	Power assisted (engine revolution sensing) ball and nut	Power assisted (engine revolution sensing) ball and nut	Power assisted (engine revolution sensing) ball and nut
Turning circle	kerb to kerb	12.6	12.6	12.6	12.6	12.6	12.6
Tyres		235/75R15 109S	235/75R15 109S	235/75R15 109S	245/70R16 111S	235/75R15 109S	245/70R16 111S
Wheels		15 x 6.5 JJ (styled steel)	15 x 6.5 JJ (styled steel)	15 x 6.5 JJ (styled steel)	16 x 7.0 J (alloy)	15 x 6.5 JJ (styled steel)	16 x 7.0 J (alloy)
Spare tyre/wheel		Full size (styled steel)	Full size (styled steel)	Full size (styled steel)	Full size (alloy)	Full size (styled steel)	Full size (alloy)
Dimensions							
Overall length		4,841	4,841	5,169	5,169	5,169	5,169
Overall width		1,807	1,807	1,807	1,807	1,807	1,807
Overall height		1,743	1,743	1,743	1,750	1,755	1,762
Wheelbase		3,000	3,000	3,000	3,000	3,000	3,000
Ground clearance	unladen	207	207	207	207	207	207
Track	front	1,445	1,445	1,445	1,475	1,445	1,475
	rear	1,440	1,440	1,440	1,470	1,440	1,470
Tray length		-	-	1,753	1,753	1,530	1,530
Tray width		-	-	1,456	1,456	1,456	1,456
Tray height		-	-	465	465	465	465
Tray floor height to ground		-	-	797	804	798	805
Back of cab to rear axle		1,207	680	680	680	457	457
Overhang	front	884	884	884	884	884	884
	rear	960	960	1,285	1,285	1,285	1,285
Wading depth		750	750	750	750	750	750
Approach angle		32	32	32	32	32	32
Departure angle		27	27	26	26	26	26
Ramp breakover angle		28	28	28	28	28	28
Leg room	front	1,049	1,068	1,068	1,068	1,068	1,068
Shoulder room	front	1,405	1,405	1,405	1,405	1,405	1,405
Head room	front	1,012	1,012	1,012	1,012	1,012	1,012
Weights & Capacities							
Gross Combined Mass (GCM) ²	man	5,500	5,500	5,500	5,500	5,500	5,500
	auto	-	-	-	-	-	4,875
Gross Vehicle Mass (GVM)	man	3,044	3,050	3,050	3,036	3,025	3,013
	auto	-	-	-	-	-	3,027
Kerb weight	man	1,614-1,624	1,692-1,696	1,840-1,845	1,817	1,872-1,876	1,855
	auto	-	-	-	-	-	1,864
Payload ³	man	1,430-1,420	1,358-1,354	1,210-1,205	1,219	1,153-1,149	1,158
	auto	-	-	-	-	-	1,163

Axle capacity	front	1,430	1,430	1,430	1,430	1,430	1,430
	rear	1,850	1,850	1,850	1,850	1,850	1,850
Towing capacity ⁴	braked	2,500	2,500	2,500	2,500	2,500	2,500
	unbraked	750	750	750	750	750	750
Seating capacity		2 or 3	4	4	4	5	5

1 Fuel consumption figures are based on ADR81/01 test results. They are useful in comparing the fuel consumption of different vehicles. They may not be the fuel consumption achieved in practice. This will depend on traffic and road conditions and how the vehicle is driven.

2 Gross Combined Mass (GCM) is the total permissible combined weight of the vehicle and trailer/caravan being towed including occupants, fuel and cargo.

3 The weight of any vehicle occupants, options, accessories, modifications, cargo and towball downforce must be included when calculating payload weight.

4 Subject to State or Territory regulations. When towing more than 1,800kg a load-levelling device must be fitted.